

Hankison DKC Series Desiccant Dryer

[Print this page](#)

[Close this page](#)



The HANKISON DKC Series adsorption dryer has a compact design, which makes it suitable for wall mounting and is very easy to operate. Supplied with Pre and After filter.

The HANKISON DKC Series heatless regenerative adsorption dryers are suitable for flow rates from 9 m³/h to 45 m³/h.

Operating Pressure: 3 - 10 bar
Inlet Temperature: 2 - 50 Degree C
Ambient Temperature: 2 - 45 Degree C
Pressure Dew Point: -40 Degree C
Desiccant: Activated Alumina
Medium: Compressed Air
Housing Material: Steel Construction
Colour: Blue
Location: Indoors
Pre Filter: 0.01 um
After Filter: 1 um

Model	Flow Rate	Connection	Order Code	Price
DKC 9	9 m ³ /h	3/8" BSP	227601	£2,542.50
DKC 17	17 m ³ /h	3/8" BSP	227602	£2,645.01
DKC 25	25 m ³ /h	3/8" BSP	227603	£2,852.51
DKC 35	35 m ³ /h	3/8" BSP	227604	£3,152.50
DKC 45	45 m ³ /h	1/2" BSP	227605	£3,226.25

(All Prices Exclude VAT)

CompressorMan - 45 Swadlincote Road, Woodville, South Derbyshire, , DE11 8DE
Tel: 07904 471183
Email: info@compressormanshop.co.uk Web: www.compressormanshop.co.uk